

# RAVAS-310

## A PALLET TRUCK SCALE FROM THE LEADER IN MOBILE WEIGHING

INCREASES EFFICIENCY AND SIMPLIFIES LOGISTIC PROCESSES, SAVES TIME AND SPACE

NTEP-APPROVED INTEGRATED PRINTER STANDARD

**BACKLIGHT INDICATOR FOR EASIER READ OUT** 

FOR CHECKING INCOMING GOODS, DOSING AND MIXING, DETERMINING SHIPPING WEIGHTS, COUNTING PARTS AND DATA COMMUNICATION

PIECE COUNTING PROGRAM WITH PIECE WEIGHT SAMPLING

THREE DIFFERENT COMMUNICATION PROTOCOLS FOR DATA TRANSFER TO HANDHELD TERMINAL, PC OR WMS

HIGH ACCURACY: MAXIMUM ERROR 0.1% OF THE APPLIED WEIGHT

EASILY EXCHANGEABLE BATTERY PACK FOR CONTINUOUS USE; CHARGER INCLUDED

## **FUNCTIONS**

- Automatic and manual zero correction
- Gross/net weighing
- Automatic and manual tare
- ◆ Totalling with sequence number
- ID-code entry (5-digit)
- Piece counting by sampling
- Piece counting by entry of piece weight
- Printing of date, time, counted pieces, gross/net weight, total weight
- Internal clock
- Error messages in display
- Automatic shut off after 30 minutes of non-use
- Lbs/kg toggle function





## **DIMENSIONS**

Fork length 47.5 inch Fork width 6.7 inch Minimum fork height 3.25 inch Minimum space between floor and forks 0.87 inch D Maximum fork height 8 inch Lifting height 4.75 inch Width over forks 27 inch F Height to top indicator 30 inch

#### PRECISION STANDARD VERSION

Max. inaccuracy : 0.1% of the applied weight

Graduation : 3,000 lbs: graduation 2.0 lbs

: 5,000 lbs: graduation 5.0 lbs

## STANDARD SPECIFICATIONS

Weighing capacity : 5000 lbs

Display : LCD, height 0.7 inch, with backlight and

date and time memory

Keypad : 5 function keys;

on / off key, piece counting, print, tare,

zero

Printer : Thermal printer

Protection class : load cells and cabling NEMA 5,

indicator NEMA 4

Steering wheels : polyurethane Loading wheels : polyurethane, single

Color : red (RAL 3000), epoxy painted

Own weight : 285 lbs

Battery : 12 Vdc / 1.2 Ah industrial battery pack,


exchangeable and rechargeable Battery;

charger included

Battery life : 35 hours, low voltage indication Charger : 110/120 Volt / 12 Vdc - 300 mA

Charging time : approximately 6 hours

Pump : quick lift



Indicator 310		
Print example		
CODE	12345	
B/G	1234	lb
T	34	lb
N	1200	lb
Piece counting example		
PcWt	1200	lb
Qty	1200	Pcs
Total print example		
Tot. B/G	1234	lb
Tot. T	34	lb
Tot. N	1200	lb
Nr.		1
10/07/06		17:45



http://www.material-handling.com/ravas-149.html

**Cherry's Industrial Equipment: 877-350-2729** 

## **OPTIONS WEIGHING SYSTEM**

- Bluetooth<sup>®</sup> signal output
- RAVAS Uni Mobile software for integration with Microsoft Windows® CE 5.0 / Mobile 5.0 platforms
- NTEP approval 3000 lbs x 2 lb
- Multi-range graduation:

0-500 lbs x 0.5 lb

500-1000 lbs x 1 lb

1000-5000 lbs x 2 lbs

■ Extra rechargeable battery

## **OPTIONS HAND PALLET TRUCK**

☐ Width 21 inch